









ELISSA URBEN 5W-40 SN/CF

ENGINE OIL SYNTHETIC

-  QUICK START IN ALL WEATHER CONDITIONS
-  EXCELLENT FILTERABILITY
-  HIGH VISCOSITY INDEX
-  HIGH PERFORMANCE PROPERTIES
-  SURFACE PROTECTION AGAINST CORROSION
-  HIGH LEVEL OF PURITY

ELISSA URBEN 5W-40 SN/CF is a fully synthetic multi-purpose premium-class engine oil, intended for use in any light motor vehicles. It works in both petrol and diesel engines with pump-injector units, turbochargers and the latest exhaust gas treatment systems, including those with particulate filters and catalytic converters. This oil is perfect for city cars and the start-stop driving style of urban life, with frequent stops at traffic lights, standing in traffic jams, followed by the subsequent starting.

ADVANTAGES


- high-performance detergent additive package prevents formation of lacquer and soot deposits on parts of the engine and guarantee their absolute cleanliness;
- perfect lubrication properties of the oil provide optimal oil film thickness at various hard operating modes of the engine;
- due to exclusive dispersing capacity, soot decomposes and its particles remain in suspended state during the whole service life, from change to change. And particles don't accumulate in internal volume of engine, don't choke in filters and valves;
- has perfect neutralizing ability and provides reliable protection of lubricated surfaces from corrosion;
- stands out for its stable viscosity and high fluidity, guaranteeing quick engine start at cold climate conditions;
- its operational characteristics exceed requirements of most of similar products from Russian and international manufacturers.

RECOMMENDED FOR

- Modern four-stroke engines in passenger cars and commercial vehicles.
- The start-stop driving style of urban life.
- All-season use in various climate zones.
- Ensuring energy and environmental safety in populated areas.
- Increasing the service life of the parts of the cylinder-piston block.



PHYSICAL AND CHEMICAL INDICATORS

	161
	9,5
	220
	-37
	1,36
	0,861
	13,8

CONFORMS TO THE REQUIREMENTS OF

API SN/CF | ACEA A3/B3, A3/B4
 Renault RN 0700/0710 | OJSC 'AVTOVAZ' | PSA B71 2296 | MB-Approval 229.31/229.5/229.51 | VW 502.00/505.00/505.01 | BMW Long life-01 | GM Dexos-2; GM-LL-B-025 | PSA B71 2296 | Fiat 9.55535-N2 | Porsche A40 | Opel GM-LL-B-025.

QUALITY LEVEL

ELISSA URBEN ACEA A3/B3, A3/B4; API SN
 STO 064 72266-005-2019 "Engine oils. Classification and designation».